



REGINA

Image shown 1200 x 550 Brushed Brass - Black

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C		RRP PRICES EX.VAT
						Btu	Watts	
800	550	515	63.5	151	C/E/D	3852	1130	£510.00
1200	550	515	63.5	151	C/E/D	4959	1454	£620.00




- chrome
- black
- chrome
- white

ASHEN

Image shown 1000 x 490 White - Chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C		RRP PRICES EX.VAT
						Btu	Watts	
400	490	450	72-87	163-178	C/E/D	1120	328	£380.00
700	490	450	72-87	163-178	C/E/D	1861	546	£458.00
1000	490	450	72-87	163-178	C/E/D	2728	800	£530.00



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL
For pipe center measurement including valves add/subtract 90mm accordingly



chrome

VICTORIA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C		RRP PRICES EX.VAT
						Btu	Watts	
960	675	528	105	230	C/E/D	4469	1311	£414.00





chrome

ALICIA

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C		RRP PRICES EX. VAT
						Btu	Watts	
950	475	330	95	235	C	2812	825	£375.00



Material
Steel

5 Year
Guarantee



Next Working
Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL
For pipe center measurement including valves add/subtract 90mm accordingly



OXFORD

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C		RRP PRICES EX.VAT
						Btu	Watts	
960	500	373	125	180	C	3365	987	£375.00





CAMDEN

Image shown 505 x 770 Chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C		RRP PRICES EX.VAT
						Btu	Watts	
505	675	675	50	260	C	1989	583	£350.00
505	770	770	50	260	C	2470	724	£375.00



Material Steel

5 Year Guarantee



Next Working Day Delivery



C: CENTRAL HEATING | E: ELECTRIC | D:DUAL FUEL
For pipe center measurement including valves add/subtract 90mm accordingly



25mm
TUBES



chrome

DIVA - 25mm TOWEL RAIL

Image shown 1200 x 500 Chrome Curved

CHROME FLAT

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C	
						Btu	Watts
600	300	260	70-85	85-100	C/E/D	557	163
800	300	260	70-85	85-100	C/E/D	672	197
1200	300	260	70-85	85-100	C/E/D	1179	346
1600	300	260	70-85	85-100	C/E/D	1625	477
800	400	360	70-85	85-100	C/E/D	848	249
1000	400	360	70-85	85-100	C/E/D	1236	362
1200	400	360	70-85	85-100	C/E/D	1623	476
1600	400	360	70-85	85-100	C/E/D	2016	591
1800	400	360	70-85	85-100	C/E/D	2221	651
800	450	410	70-85	85-100	C/E/D	904	265
1200	450	410	70-85	85-100	C/E/D	1707	501
1800	450	410	70-85	85-100	C/E/D	2449	718
800	500	460	70-85	85-100	C/E/D	1015	298
1000	500	460	70-85	85-100	C/E/D	1411	414
1200	500	460	70-85	85-100	C/E/D	1807	530
1400	500	460	70-85	85-100	C/E/D	2040	598
1600	500	460	70-85	85-100	C/E/D	2352	690
1800	500	460	70-85	85-100	C/E/D	2713	796
800	600	560	70-85	85-100	C/E/D	1117	328
1000	600	560	70-85	85-100	C/E/D	1525	447
1200	600	560	70-85	85-100	C/E/D	1955	573
1400	600	560	70-85	85-100	C/E/D	2256	662
1600	600	560	70-85	85-100	C/E/D	2558	750
1800	600	560	70-85	85-100	C/E/D	2915	855
800	750	710	70-85	85-100	C/E/D	1257	369
1200	750	710	70-85	85-100	C/E/D	2107	618
1800	750	710	70-85	85-100	C/E/D	3157	926

CHROME CURVED

800	400	360	70-85	85-100	C/E/D	848	249
1000	400	360	70-85	85-100	C/E/D	1236	362
1200	400	360	70-85	85-100	C/E/D	1623	476
1600	400	360	70-85	85-100	C/E/D	2016	591
1800	400	360	70-85	85-100	C/E/D	2221	651
800	450	410	70-85	85-100	C/E/D	904	265
1200	450	410	70-85	85-100	C/E/D	1707	501
1800	450	410	70-85	85-100	C/E/D	2449	718
800	500	460	70-85	85-100	C/E/D	1015	298
1000	500	460	70-85	85-100	C/E/D	1411	414
1200	500	460	70-85	85-100	C/E/D	1807	530
1400	500	460	70-85	85-100	C/E/D	2040	598
1600	500	460	70-85	85-100	C/E/D	2352	690
1800	500	460	70-85	85-100	C/E/D	2713	796
800	600	560	70-85	85-100	C/E/D	1117	328
1000	600	560	70-85	85-100	C/E/D	1525	447
1200	600	560	70-85	85-100	C/E/D	1955	573
1400	600	560	70-85	85-100	C/E/D	2256	662
1600	600	560	70-85	85-100	C/E/D	2558	750
1800	600	560	70-85	85-100	C/E/D	2915	855
800	750	710	70-85	85-100	C/E/D	1257	369
1200	750	710	70-85	85-100	C/E/D	2107	618
1800	750	710	70-85	85-100	C/E/D	3157	926



black

DIVA BLACK FLAT

Image shown 1200 x 500 Black

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C	
						Btu	Watts
800	400	360	70-85	85-100	C/E/D	1239	363
1200	400	360	70-85	85-100	C/E/D	2369	695
1800	400	360	70-85	85-100	C/E/D	3265	957
800	500	460	70-85	85-100	C/E/D	1487	436
1200	500	460	70-85	85-100	C/E/D	2657	779
1800	500	460	70-85	85-100	C/E/D	3961	1162
800	600	560	70-85	85-100	C/E/D	1643	482
1200	600	560	70-85	85-100	C/E/D	2870	842
1800	600	560	70-85	85-100	C/E/D	4284	1256



anthracite



DIVA ANTHRACITE FLAT

Image shown 1200 x 500 Anthracite

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C	
						Btu	Watts
800	400	360	70-85	85-100	C/E/D	1239	363
1200	400	360	70-85	85-100	C/E/D	2369	695
1800	400	360	70-85	85-100	C/E/D	3265	957
800	500	460	70-85	85-100	C/E/D	1487	436
1200	500	460	70-85	85-100	C/E/D	2657	779
1800	500	460	70-85	85-100	C/E/D	3961	1162
800	600	560	70-85	85-100	C/E/D	1643	482
1200	600	560	70-85	85-100	C/E/D	2870	842
1800	600	560	70-85	85-100	C/E/D	4284	1256



white

DIVA WHITE FLAT

Image shown 1200 x 500 White

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C	
						Btu	Watts
800	300	260	70-85	85-100	C/E/D	1085	318
1200	300	260	70-85	85-100	C/E/D	1927	565
800	400	360	70-85	85-100	C/E/D	1239	363
1200	400	360	70-85	85-100	C/E/D	2369	695
1800	400	360	70-85	85-100	C/E/D	3265	957
800	500	460	70-85	85-100	C/E/D	1487	436
1200	500	460	70-85	85-100	C/E/D	2657	779
1800	500	460	70-85	85-100	C/E/D	3961	1162
800	600	560	70-85	85-100	C/E/D	1643	482
1200	600	560	70-85	85-100	C/E/D	2870	842
1800	600	560	70-85	85-100	C/E/D	4284	1256



CAPO CHROME FLAT & CURVED OPTIONS

Image shown 1200 x 500 Chrome

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C	
						Btu	Watts
800	400	355	70-85	85-100	C/E/D	749	220
1000	400	355	70-85	85-100	C/E/D	960	282
1200	400	355	70-85	85-100	C/E/D	1075	315
1600	400	355	70-85	85-100	C/E/D	1421	417
1800	400	355	70-85	85-100	C/E/D	1502	440
800	500	455	70-85	85-100	C/E/D	886	260
1000	500	455	70-85	85-100	C/E/D	1101	323
1200	500	455	70-85	85-100	C/E/D	1269	372
1600	500	455	70-85	85-100	C/E/D	1675	491
1800	500	455	70-85	85-100	C/E/D	1836	538
800	600	555	70-85	85-100	C/E/D	1027	301
1000	600	555	70-85	85-100	C/E/D	1243	365
1200	600	555	70-85	85-100	C/E/D	1471	431
1600	600	555	70-85	85-100	C/E/D	1943	570
1800	600	555	70-85	85-100	C/E/D	2982	874



CAPO BLACK FLAT

Image shown 1200 x 500 Black

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C	
						Btu	Watts
800	400	355	70-85	85-100	C/E/D	1105	324
800	500	455	70-85	85-100	C/E/D	1311	384
800	600	555	70-85	85-100	C/E/D	1528	448
1000	400	355	70-85	85-100	C/E/D	1420	416
1000	500	455	70-85	85-100	C/E/D	1640	481
1000	600	555	70-85	85-100	C/E/D	1848	542
1200	400	355	70-85	85-100	C/E/D	1598	469
1200	500	455	70-85	85-100	C/E/D	1900	557
1200	600	555	70-85	85-100	C/E/D	2180	639
1600	400	355	70-85	85-100	C/E/D	2117	621
1600	500	455	70-85	85-100	C/E/D	2500	733
1600	600	555	70-85	85-100	C/E/D	2895	849
1800	400	355	70-85	85-100	C/E/D	1868	548
1800	500	455	70-85	85-100	C/E/D	2770	812
1800	600	555	70-85	85-100	C/E/D	3259	956



anthracite

CAPO ANTHRACITE FLAT

Image shown 1200 x 500 Anthracite

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C	
						Btu	Watts
800	400	355	70-85	85-100	C/E/D	1105	324
800	500	455	70-85	85-100	C/E/D	1311	384
800	600	555	70-85	85-100	C/E/D	1528	448
1000	400	355	70-85	85-100	C/E/D	1420	416
1000	500	455	70-85	85-100	C/E/D	1640	481
1000	600	555	70-85	85-100	C/E/D	1848	542
1200	400	355	70-85	85-100	C/E/D	1598	469
1200	500	455	70-85	85-100	C/E/D	1900	557
1200	600	555	70-85	85-100	C/E/D	2180	639
1600	400	355	70-85	85-100	C/E/D	2117	621
1600	500	455	70-85	85-100	C/E/D	2500	733
1600	600	555	70-85	85-100	C/E/D	2895	849
1800	400	355	70-85	85-100	C/E/D	1868	548
1800	500	455	70-85	85-100	C/E/D	2770	812
1800	600	555	70-85	85-100	C/E/D	3259	956



CAPO WHITE FLAT

Image shown 1200 x 500 White Flat

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C	
						Btu	Watts
800	400	355	70-85	85-100	C/E/D	1105	324
800	500	455	70-85	85-100	C/E/D	1311	384
800	600	555	70-85	85-100	C/E/D	1528	448
1000	400	355	70-85	85-100	C/E/D	1420	416
1000	500	455	70-85	85-100	C/E/D	1640	481
1000	600	555	70-85	85-100	C/E/D	1848	542
1200	400	355	70-85	85-100	C/E/D	1598	469
1200	500	455	70-85	85-100	C/E/D	1900	557
1200	600	555	70-85	85-100	C/E/D	2180	639
1600	400	355	70-85	85-100	C/E/D	2117	621
1600	500	455	70-85	85-100	C/E/D	2500	733
1600	600	555	70-85	85-100	C/E/D	2895	849
1800	400	355	70-85	85-100	C/E/D	1868	548
1800	500	455	70-85	85-100	C/E/D	2770	812
1800	600	555	70-85	85-100	C/E/D	3259	956

brushed
brass

OTTONE BRUSHED BRASS

Image shown 1600 x 500 Brushed Brass

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C		RRP PRICES EX. VAT
						Btu	Watts	
800	500	455	70-85	85-100	C/E/D	886	260	£249.00
1200	500	455	70-85	85-100	C/E/D	1269	372	£339.00
1600	500	455	70-85	85-100	C/E/D	1675	491	£439.00
800	600	555	70-85	85-100	C/E/D	1027	301	£259.00
1200	600	555	70-85	85-100	C/E/D	1471	431	£349.00
1600	600	555	70-85	85-100	C/E/D	1943	570	£459.00

Material
Steel
5 Year
Guarantee

 Next Working
Day Delivery

EN 442

C: CENTRAL HEATING | E: ELECTRIC | D: DUAL FUEL
 For pipe center measurement including valves add/subtract 90mm accordingly



OTTONE GUN METAL

Image shown 1600 x 500 Gun Metal

Overall Height mm	Dimension Width mm	Pipe Centres mm	Wall to Pipe Centres mm	Wall Distance mm	Fuel Type	Heat Outputs ΔT 60°C		RRP PRICES EX.VAT
						Btu	Watts	
800	500	455	59-69	74-84	C/E/D	886	260	£249.00
1200	500	455	59-69	74-84	C/E/D	1269	372	£339.00
1600	500	455	59-69	74-84	C/E/D	1675	491	£439.00

800	600	555	59-69	74-84	C/E/D	1027	301	£259.00
1200	600	555	59-69	74-84	C/E/D	1471	431	£349.00
1600	600	555	59-69	74-84	C/E/D	1943	570	£459.00